

TYPE 102



Operating Limits:

Pressure: 1MPa

Speed: 10m/s

Temperature: -30C ~ 200C

Spring & Other Parts: SUS316

Rotary Ring: SUS/Sic/Tc

Stationary Ring: Carbon/Sic/Tc

O -Ring: NBR/EPDM/VITON/PTEF

Option: Left-hand spring.

א. עבודה	ק. קבוע	ק. סובב	ק. ציר
15	18.1	19	10
18	20.6	21	12
22	23.1	23	14
22	26.9	24	15
23	26.9	26	16
24	30.9	29	18
25	30.9	31	19
25	30.9	31	20
25	35.4	33	22
27	35.4	35	24
27	38.2	36	25
29	43.3	40	28
30	43.3	43	30
30	43.2	46	32
39	53.5	48	33
39	53.5	49	35
39	60.5	53	38
39	60.5	56	40
39	60.5	59	42
41	60.5	59	43
41	65.5	61	45
41	65.5	64	48
45	72.5	66	50
47	72.5	71	55
49	79.3	78	60
51	84.5	84	65
51	89.5	90	70
57	94.5	98	75
59	99.5	100	80

המידות במ"מ

דגם TYPE 102 תואם

Roten 2, Eulopa 2 , TEKHNI SEAL 400