



חברת פרוסיל טכנולוגיות בע"מ מתמחה בתחום האטמים
ביניהם אטמים שטוחים לאוגנים מחומרים שונים.

בתחום זה אנו מייבאים משדרגים מייצרים ומשווקים אטמים !!!

אנו מספקים פתרונות לכלל השימושים ולמגון תחומים,
תעשייה, מזון, רפואה, חקלאות כלים הנדסיים ועוד ...

Style	Structure	Thik	Material	M. Material
6000	Without rings			
600 IR	With inner ring	2~4	Graphite / PTFE	304, 316, Hast
6000 OR	with outer ring	mm.		
6000 IOR	With inner&outer rings			



Style CG - Utilizes an external ring which accurately centers gasket on flange face, provides additional radial strength to prevent gasket blow-out and acts as a compression stop. A general purpose gasket suitable for use with flat face and raised face flanges up to and inclusive of class 2500. See note at bottom of page 8 for inner ring requirements.



Style CGI - A Style CG gasket fitted with internal ring which gives an additional compression limiting stop and provides heat and corrosion barrier protecting gasket windings and preventing flange erosion. Suitable for use with flat face and raised face flanges. See note at bottom of page 8 for inner ring requirements.



Style R - Basic construction type. Inner and outer diameters are reinforced with several plies of metal without filler to give greater stability and better compression and sealing characteristics. Suitable for tongue and groove or male and female or grooved to flat face flange assemblies.



Style RIR - Solid inner metal ring acts as a compression stop and fills the annular space between flange bore and the inside diameter of the gasket. Designed to prevent accumulation of solids, reduce turbulent flow of process fluids and minimize erosion at flange faces. Suitable for male and female pipe flanges.

As a leading supplier of sealing products and accessories we supply metric and inch versions of any size and material of hydraulic seals.

Customer provided items may also be include in the assembled kit.

